

# JNJ Industries, Inc.

290 Beaver Street

Franklin, MA 02038

Phone (508) 553-0529 \* Fax (508) 553-9973

www.jnj-industries.com \* e-mail: sales@jnj-industries.com

## MATERIAL SAFETY DATA SHEET

GlobalTech®

PRODUCT CODE: MMC

Date of Last Revision: 6/24/03

### Terminator Mold and Mildew Cleaner/MMC

**FOR CHEMICAL EMERGENCY call INFOTRAC at 1-800-535-5053**

24 Hrs. per day, 7 days per week

DOT HAZARD CLASSIFICATION: NOT REGULATED  
DOT PROPER SHIPPING NAME: NOT REGULATED BY D.O.T.

#### SECTION I - COMPOSITION AND INFORMATION ON INGREDIENTS:

INGREDIENTS	C.A.S. NUMBER	EXPOSURE LEVELS		PERCENTAGE
		PPM	AGENCY TYPE	
Sodium hypochlorite	7681-52-9	Not determined		
Sodium chloride	7647-14-5	Not determined		

Specific Chemical identities withheld under Trade Secret Status

#### SECTION II - HAZARDS IDENTIFICATION: symptoms/effects of overexposure

**INHALATION (BREATHING):** Coughing and irritation of the respiratory tract.

**INGESTION (SWALLOWING):** Can cause corrosion of mucous membranes, perforation of esophagus and stomach, laryngeal edema; may lead to convulsion, coma or death.

**SKIN CONTACT:** Severe irritation and reddening.

**EYE CONTACT:** Severe irritation and reddening.

**SIGNS AND SYMPTOMS OF OVEREXPOSURE:**

**skin and eyes:** severe irritation and reddening.

**respiratory tract:** cough and irritation.

**ingestion:** convulsions, coma and death.

#### SECTION III - FIRST AID MEASURES:

**INHALATION (BREATHING):** If inhaled, move immediately from exposure area.

**INGESTION (SWALLOWING):** If swallowed, drink milk or raw egg white. Do not induce vomiting. If spontaneous vomiting occurs, keep head below hips to prevent aspiration to lungs, which could cause serious damage. Seek medical attention.

**SKIN CONTACT:** Remove contaminated clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and/or persists, seek medical attention.

**EYE CONTACT:** If splashed in eye, immediately flush affected area with clean water for 10 minutes. If redness develops or persists, seek medical attention.

#### SECTION IV - FIRE FIGHTING MEASURES:

No fire or explosion hazards, unless contacted by oxidizers.

---

---

## SECTION V - STORAGE, HANDLING AND SPECIAL PRECAUTIONS:

---

---

Empty containers are hazardous and should be treated accordingly. Avoid contact of product with amines, bases, and reactive metals, sulfides and cyanides.

---

---

## SECTION VI - EXPOSURE CONTROLS - PERSONAL PROTECTION:

---

---

**PROTECTIVE CLOTHING/GLOVE:** Gloves, keep sleeves rolled down.

**EYE PROTECTION:** Safety glasses/goggles.

---

---

## SECTION VII - PHYSICAL AND CHEMICAL PROPERTIES:

---

---

<b>Boiling Point:</b>	213°F	<b>Vapor Density (air=1):</b>	N/D
<b>Evaporation Rate (n-butyl acetate=1.0):</b>	N/A	<b>% Volatile:</b>	80
<b>Vapor Pressure:</b>	same as water	<b>Solubility in Water:</b>	100%
<b>Specific Gravity:</b>	1.03 (8.53 lb/gal)	<b>Odor:</b>	bleach like
<b>Appearance:</b>	yellow		
<b>Flash Point:</b>	none		
<b>VOC content:</b>	0.0 lbs/gal		

---

---

## SECTION VIII - STABILITY AND REACTIVITY:

---

---

**STABILITY:** Stable.

**INCOMPATIBILITY (materials to avoid):** Oxidizers.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Will not occur.

**HAZARDOUS POLYMERIZATION:** Will not occur.

---

---

## SECTION IX - DISPOSAL CONSIDERATIONS:

---

---

Waste treat used material in compliance with all applicable local, state and federal regulations.

---

---

## SECTION X - OTHER INFORMATION:

---

---

NFPA Codes	<b>HEALTH:</b>	3	<b>HAZARD RATING SCALE</b>	
	<b>FIRE:</b>	0	0=insignificant	1=slight
	<b>REACTIVITY:</b>	0	2=moderate	3=high
			4=extreme	

---

---

## DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:

---

---

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the material. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk for his use thereof. JNJ accepts no responsibility for any personal injury, property damage, or other type of loss due to negligence or otherwise resulting from the use or handling of this material. Manufacturer's Liability is limited to the net purchase price of the product or at manufacturer's option to the replacement of the product upon its return to us.